

aquaforte

PRESERVATION AND MAINTENANCE OF SOLID® WASHBASINS AND BATHTUBS

In order to preserve the original surface characteristics of SOLID® using a cloth and soapy water to remove most stains and the dirt that may have deposited.

In case of more resistant dirty use common detergents: gel detergents are particularly recommended in combination with a scrub sponge of the Scotch Brite® type. Thoroughly rinse the surface with abundant water. In this way, you can make sure the original distinctive matt finish of SOLID® is safely preserved.

This surface is highly resistant to stains in general. Nevertheless, we do recommend NOT to use aggressive chemicals such as acetone, trichloroethylene or strong acids (e.g. muriatic acid) or strong bases (e.g. caustic soda), industrial detergents, solvents used in wall painting or very aggressive substances for clearing sink drains.

Suitable products are detergent creams or powders such as CIF®, VIM® or similar products which contain microgranules that scour the surface. Denatured ethyl alcohol can also be used, making sure the surface is then rinsed thoroughly.

Some substances such as ink, cosmetics and dyes may stain the surface of SOLID® if in prolonged contact with the material, the same could happen with cigarette burns.

In these case small surface damage of SOLID® can be restored using a Scotch Brite® (3M registered trademark) scrub sponge combined with a common abrasive cleaner. If the damage is still visible, smooth again the area using extra-fine sandpaper.

We do recommend not to use this product at water temperature above 55° C (130° F). The Manufacturer shall not be liable for any damages that may result from the improper use of the product.